



SANTARO 7.0 OF PCT IPS outdoor


ARM Cortex-A9 Rear Mount



TECHNICAL SPECIFICATION

SANTARO 7.0 OF PCT IPS outdoor

	x1	x2
CPU		
CPU Type	i.MX6Solo	i.MX6Dual
Core Class	ARM Cortex - A9	
Core Clock	1 GHz	
Features	NEON for SIMD media acceleration and VFP operations; Multi-format HD 1080p video decoder and HD 720p video encoder hardware engine; L1 cache, 32 KB for instruction, 32 KB for data	
HW Accelerators	512 KB L2 cache Open VG 1.1 (Emulated on 3D GPU)	1 MB L2 cache Open VG 1.1
RTC	Accuracy: +/- 30 ppm at 25°C	
Memory		
eMMC Flash	4 GB eMMC Flash	
RAM Standard	1 GB 32 bit DDR3L	1 GB 64 bit DDR3L
SD Card Slot	4 bit MMC/SDIO/SD/SDHC	
Operating Systems		
Supported OS	Windows Embedded Compact 7/2013, Linux Yocto, Android	
Communication Interfaces		
Digital I/O	2x In, 2x Out (0.7 A)	
Network	1x 10/100 Mbit/s Ethernet (RJ-45)	
USB 2.0	1x 480 Mbit/s Host (Type A) 1x 480 Mbit/s OTG (Type Micro-AB)	
CAN Fieldbus / RS-485	1x CAN (ISO/DIS 11898) + 1x RS-485	1x CAN (ISO/DIS 11898) + 1x RS-485 galvanic isolated
RS-232	2x RS-232 [RX/TX/CTS/RTS]	
Synchronous Serial Interfaces	SPI up to 12 chip selects; I ² C; Matrix keypad up to 8 x 8	
Video		
Video output		Full HD micro HDMI
Audio		
Speaker output	1x speaker [connector], 1.5W RMS (8Ω)	
Audio Internal	1x speaker 0.3 W RMS (8Ω)	
Display and Touch		
Size	7 inch/177.8 mm	
Resolution	800 x 480 pixel	
Brightness	Typ. 1000 cd/m ²	
Backlight Control	Ambient Light Sensor	
Backlight Lifetime	Typ. 70 000 h	
Viewing Angle	85°, 85°, 85°, 85° (UDRL)	
Color	24 bit (16.7 Mio. colors)	
Touch	projected capacitive multi touch	
Housing		
Front	5.0 mm toughened glass, Pantone black C	
Frame	None	
Rear	2.5 mm 1.4016 stainless steel, foam seal	
Ingress Protection	Front IP 20/Rear IP20	
Device Dimensions		
W x H x D	220.5 x 150.9 x 43.4 mm	
Weight	tbd.	
Power Supply		
Supply Voltage	Nom. 13 to 32 V DC	
Consumption	Typ. 9.1 W; max. 26.8 W	
Typical Environmental Conditions		
Storage Temp.	-20 to +70 °C	
Operating Temp.	-20 to +60 °C	
Humidity	5 to 90 % RH	



Online support on www.garz-fricke.com

„This product can be modified by alternative assembly. Please contact us for available options.“